

Installation Instructions for a 20% Center Console

Opening Console: Has a compartment on the top section which allows you to store small items.

- Locate the longest cover, with cut outs for cup holders(if applicable)
 - You will need to feed the top section of the console in between the back and the cushion
 - Align the front section with the cup holders
 - Open the console and attach the Velcro straps going across
 - Pull the back section firmly and slide it over the lid and attach the Velcro's going across
 - Close the lid and make sure all the seams are properly aligned
- ***Note some covers will have Velcro's on the side flap which will attach on the back section with Velcro's
- ***Some backrest covers will have a zipper which is made to all the integrated seat belt to be installed
- ***Some vehicles do not have cup holders so you will need to located the cover by identifying the longest cover



Solid Center Console – Top center console with NO compartment

- Located the cover with the cup holder cut out if applicable
 - Remove the headrest cover
 - Slide the cover over the center backrest and attach the Velcro's together as shown
- *** Some backrest covers will have a zipper which is made to all the integrated seat belt to be installed



Installation Instructions for a 20% Center Console

Center Cushion W/ Under Seat Storage – The lower seat has a compartment

- Locate the cover with a cut out on the front section and a few velcro strips under neath
 - Align the cover accordly use the cut out as guidance
 - First attach the front velcro strips under the cushions carpeting
 - Then attach the side velcro strips
 - Finally attach the velcro located on the back section of the cover
- ***Some covers will only have 2 velcros which attach together..this will apply to most older vehicles



Center Cushion W/O Under Seat Storage – The lower seat has no compartment

- Locate the cushion with only ONE strip of Velcro on the back section
- Align the front section and sides properly and pull towards the back
- Firmly pull and attach Velcro to the carpeting of the vehicle